



### CLEARBOARD

This dry erase board transforms your glass surfaces in a real board for dry erase markers, while preserving total clarity and transparency.



SOLAR SCREEN® Warranty  
**10 YEARS**



Fire-resistance rating  
**M1**



Storage from -5°C to +40°C  
**3 YEARS**



REACH RoHS compliant  
**RESPECTED**

### WIDTHS AVAILABLE:

↔ **152 cm**

### TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (\*on double glazing 4-16-4)

Ultraviolet transmission	5 %
Visible light transmission	85 %

#### FRONT

Technology	PET
Thickness	90 µm
Finish	Glossy/Ultra clear

#### COMPATIBILITY

Surface(s)	Flat surface
Application type	Indoor
Printing method	UV - UV gel

#### DURABILITY

Outdoor resistance	2 years
Indoor resistance	15 years
Anti-scratch/hard coat	Yes

#### ADHESIVE

Type	PS adhesive
Performance	Removable

#### LINER


Type	Clear PET
Thickness	60µ

### APPLICATIONS

Glass surface
Showcase
Decoration
Exhibitions
Meeting room
Compatible with erasable pen

### CONSTRUCTION

1. Hard scratch resistant layer, for durability and ease of maintenance during window cleaning
2. High optical quality polyester
3. Reinforced PS adhesive to accompany the elasticity of the film in case of impact, glass polymerization within 30 days
4. Protection release liner, disposable after installation



### MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

*Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.*