



ELEKTRO

The Elektro decorative film, featuring a large oscillating wave pattern, allows you to effectively customize your windows and glass partitions.



SOLAR SCREEN® Warranty
5 YEARS



Fire-resistance rating
M1



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant
RESPECTED

WIDTHS AVAILABLE:

↔ **152 cm**

TECHNICAL DATASHEET


Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	NC %
Visible light transmission	NC %
Reflection of external visible light	NC %
Reflection of internal visible light	NC %
Total solar energy rejected	%
Total solar energy rejected 2*	%
Solar ratio :	
Solar energy reflection	NC %
Solar energy absorption	NC %
Solar energy transmission	NC %
Reduction in Solar Glare	NC %
g-value	NC
u-value	NC
Shading coefficient	NC
Installation type : Interior	
Roll length	50 m
Film composition	PET
Thickness	40 µ

Colour from the outside : FROSTED

CONSTRUCTION

1. High optical quality polyester with printed design
2. PS adhesive, glass polymerization within 15 days
3. Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.

INSTALLATION ADVICE

Vertical installation and on standard glass surface**

Clear single pane	✓
Tinted single pane	✓
Reflective tinted single pane	✓
Clear double pane	✓
Tinted double pane	✓
Reflective tinted double pane	✓
Gas-filled double pane - Low E	✓
STADIP EXT. clear double pane	✓
STADIP INT. clear double pane	✓

✓ Yes ! Caution ✗ Not recommended

*Recommendations provided on the basis of a glazed surface covering up to 2.5m².