



MAT ACID

Mat Acid privacy films are designed to provide protection against the scrutiny of prying eyes. Whilst completely opalescent, the film still allows most natural light to pass through. Printable on any type of machine.



SOLAR SCREEN® Warranty
5 YEARS



Fire-resistance rating
M1



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant
RESPECTED

WIDTHS AVAILABLE:

↔ **152 cm**

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	> 25 %
Visible light transmission	45 %

FRONT

Technology	Polymeric PVC
Thickness	80 µm
Finish	Opalescent White

COMPATIBILITY

Surface(s)	Flat surface
Application type	Outdoor/indoor
Printing method	UV - UV gel - Aqueous print - Latex - Eco solvent

DURABILITY

Outdoor resistance	8 years
Indoor resistance	10 years
Anti-scratch/hard coat	No

ADHESIVE


Type	Acrylic solvent
Performance	Semi-permanent

LINER

Type	Cardstock
Thickness	108µ

CONSTRUCTION

- 80µ polymer PVC
- Half permanent adhesive, allowing the degassing of the actual surface, and limits the adhesive transfer during removal
- Paper release liner allowing digital cutting



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.