



WHITE PRINT PVC

The White Print PVC film can be printed on with any type of printing machine or method. It has a bubble free adhesive guaranteeing the white effect of the film.



SOLAR SCREEN® Warranty
3 YEARS



Storage from -5°C to +40°C
3 YEARS



REACH RoHS compliant
RESPECTED

WIDTHS AVAILABLE:

↔ **152 cm**

TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

| | |
|----------------------------|--------|
| Ultraviolet transmission | < 30 % |
| Visible light transmission | 9 % |

FRONT

| | |
|------------|---------------|
| Technology | Monomeric PVC |
| Thickness | 100 µm |
| Finish | Glossy white |

COMPATIBILITY

| | |
|------------------|---|
| Surface(s) | Flat surface |
| Application type | Outdoor/indoor |
| Printing method | UV - UV gel - Aqueous print - Latex - Eco solvent - Solvent |

DURABILITY

| | |
|------------------------|---------|
| Outdoor resistance | 5 years |
| Indoor resistance | 8 years |
| Anti-scratch/hard coat | No |

ADHESIVE


| | |
|-------------|----------------------|
| Type | Polyacrylate solvent |
| Performance | Removable |

LINER

| | |
|-----------|-----------|
| Type | Cardstock |
| Thickness | 140µ |

CONSTRUCTION

1. White monomer PVC
2. Removable polyacrylate solvent adhesive
3. Protection release liner, disposable after installation



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.